


LAB-232



Hedef

Router'larda Multi Area OSPF konfigurasyonu gerçekleştirerek farklı networklerin haberleşmesini sağlamak.

PC'lerin IP konfigurasyonları

PC1	VLAN 10	192.168.10.11/24	Default GateWay 192.168.10.1
PC2	VLAN 10	192.168.20.11/24	Default GateWay 192.168.20.1
PC3	VLAN 10	192.168.30.11/24	Default GateWay 192.168.30.1
PC4	VLAN 10	192.168.40.11/24	Default GateWay 192.168.40.1

Çalışma-01

Bu çalışmamızda batının en yaygın ve en popüler routing protokolü olan OSPF'i **çoklu area** altında konfigure edeceğiz.

OSPF konfigurasyonu yaparken router'larda dikkat edeceğimiz hususlar olacaktır: **network** komutu ile interfaceleri OSPF'e dahil ederken **WildCard Mask**'ı en fazla örtüşme sağlayacak şekilde yani **0.0.0.0** olarak tanımlayacağız. Cihazların **loopback** interfacelerini dağıtırken aynı zamanda bu interface IP adreslerini **Router-ID** olarak kullanacaz. Stub networkleri **passive-interface** olarak tanımlayarak bu interfacelerden OSPF Hello paketlerinin gitmesini engelleyeceğiz. Bunun hem gereksiz trafiği engellediğini hemde bir güvenlik tedbiri olduğunu belirtmek isterim.

OSPF konfigurasyonu sayesinde router'lar üzerlerindeki ve öğrendikleri networklerin bilgilerini, birbirleriyle paylaşacaklar. Bu paylaşım neticesinde PC'lerin haberleşmesi de sağlanmış olacaktır.

Router'larda OSPF'i enable ederken kullandığımız numara **Process-ID** olarak adlanır. Bunun router'lar arasında hiç bir önemi yoktur. Bu numara aynı router içinde birden fazla OSPF çalıştırılabilmemize olanak tanırken farklı process'leri de birbirinden ayırrı. Bunu vurgulamak için her router'da farklı bir process-id seçimi yaptı.

İlgili interface'i OSPF'e dahil etmenin bir diğer yöntemide interface altında konfigurasyon yapmaktadır. Biz çalışmamızda **network** komutunu kullanarak bu ihtiyacı gidersek de böyle bir seçenekinde mevcut olduğunu bilmeniz gerekmektedir.

```
R(config)#interfaces serial 0/0/0
R(config-if)# ip ospf 1 area 0
```

Bu konfigurasyon ile Serial 0/0/0 interface'i OSPF'e dahil edilmiştir.

```
R-01#configure terminal
R-01(config)#
R-01(config)#router ospf 1
R-01(config-router)#
R-01(config-router)#router-id 1.1.1.1
R-01(config-router)#passive-interface gigabitEthernet 0/0
R-01(config-router)#network 192.168.10.1 0.0.0.0 area 11
R-01(config-router)#network 1.1.1.1 0.0.0.0 area 11
R-01(config-router)#network 172.16.12.1 0.0.0.0 area 11
R-01(config-router)#end
R-01#
```

```
R-02#configure terminal
R-02(config)#
R-02(config)#router ospf 22
R-02(config-router)#
R-02(config-router)#router-id 2.2.2.2
R-02(config-router)#network 172.16.12.2 0.0.0.0 area 11
R-02(config-router)#network 2.2.2.2 0.0.0.0 area 0
R-02(config-router)#network 172.16.23.2 0.0.0.0 area 0
R-02(config-router)#end
R-02#
```

```
R-03#configure terminal
R-03(config)#
R-03(config)#router ospf 3
R-03(config-router)#
R-03(config-router)#router-id 3.3.3.3
R-03(config-router)#network 172.16.23.3 0.0.0.0 area 0
R-03(config-router)#network 3.3.3.3 0.0.0.0 area 0
R-03(config-router)#network 172.16.34.3 0.0.0.0 area 0
R-03(config-router)#end
R-03#
```

```
R-04#configure terminal
R-04(config)#
R-04(config)#router ospf 4
R-04(config-router)#
R-04(config-router)#router-id 4.4.4.4
R-04(config-router)#network 172.16.47.4 0.0.0.0 area 13
R-04(config-router)#network 4.4.4.4 0.0.0.0 area 0
R-04(config-router)#network 172.16.34.4 0.0.0.0 area 0
R-04(config-router)#network 172.16.40.4 0.0.0.0 area 12
R-04(config-router)#end
R-04#
```

```
R-05#configure terminal
R-05(config)#
R-05(config)#router ospf 5
R-05(config-router)#
R-05(config-router)#router-id 5.5.5.5
R-01(config-router)#passive-interface gigabitEthernet 0/1
R-05(config-router)#network 5.5.5.5 0.0.0.0 area 12
R-05(config-router)#network 192.168.40.1 0.0.0.0 area 12
R-05(config-router)#network 172.16.40.5 0.0.0.0 area 12
R-05(config-router)#end
R-05#
```

```
R-06#configure terminal
R-06(config)#
R-06(config)#router ospf 6
R-06(config-router)#
R-06(config-router)#router-id 6.6.6.6
R-01(config-router)#passive-interface gigabitEthernet 0/1
R-06(config-router)#network 6.6.6.6 0.0.0.0 area 12
R-06(config-router)#network 192.168.20.1 0.0.0.0 area 12
R-06(config-router)#network 172.16.40.6 0.0.0.0 area 12
R-06(config-router)#end
R-06#

R-07#configure terminal
R-07(config)#
R-07(config)#router ospf 77
R-07(config-router)#
R-07(config-router)#router-id 7.7.7.7
R-01(config-router)#passive-interface gigabitEthernet 0/0
R-07(config-router)#network 7.7.7.7 0.0.0.0 area 13
R-07(config-router)#network 192.168.30.1 0.0.0.0 area 13
R-07(config-router)#network 172.16.47.7 0.0.0.0 area 13
R-07(config-router)#end
R-07#
```

Router R-04'de IP Routing tablosuna bakalım.

R-04#**show ip route**

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2
* - candidate default, U - per-user static route, o - ODR
P - periodic downloaded static route

Gateway of last resort is not set

```
1.0.0.0/32 is subnetted, 1 subnets
O IA  1.1.1.1/32 [110/130] via 172.16.34.3, 00:00:58, Serial0/0/0
    2.0.0.0/32 is subnetted, 1 subnets
O      2.2.2.2/32 [110/129] via 172.16.34.3, 00:01:08, Serial0/0/0
        3.0.0.0/32 is subnetted, 1 subnets
O          3.3.3.3/32 [110/65] via 172.16.34.3, 00:01:08, Serial0/0/0
            4.0.0.0/32 is subnetted, 1 subnets
C              4.4.4.4/32 is directly connected, Loopback0
            5.0.0.0/32 is subnetted, 1 subnets
O              5.5.5.5/32 [110/2] via 172.16.40.5, 00:00:13, GigabitEthernet0/0
            6.0.0.0/32 is subnetted, 1 subnets
O              6.6.6.6/32 [110/2] via 172.16.40.6, 00:00:13, GigabitEthernet0/0
            7.0.0.0/32 is subnetted, 1 subnets
O              7.7.7.7/32 [110/65] via 172.16.47.7, 00:00:38, Serial0/0/1
                172.16.0.0/16 is variably subnetted, 8 subnets, 2 masks
O IA    172.16.12.0/24 [110/129] via 172.16.34.3, 00:01:08, Serial0/0/0
O      172.16.23.0/24 [110/128] via 172.16.34.3, 00:01:08, Serial0/0/0
C      172.16.34.0/24 is directly connected, Serial0/0/0
L      172.16.34.4/32 is directly connected, Serial0/0/0
C      172.16.40.0/24 is directly connected, GigabitEthernet0/0
L      172.16.40.4/32 is directly connected, GigabitEthernet0/0
C      172.16.47.0/24 is directly connected, Serial0/0/1
L      172.16.47.4/32 is directly connected, Serial0/0/1
O IA  192.168.10.0/24 [110/130] via 172.16.34.3, 00:00:58, Serial0/0/0
O  192.168.20.0/24 [110/2] via 172.16.40.6, 00:00:13, GigabitEthernet0/0
O  192.168.30.0/24 [110/65] via 172.16.47.7, 00:00:38, Serial0/0/1
O  192.168.40.0/24 [110/2] via 172.16.40.5, 00:00:13, GigabitEthernet0/0
```

R-04#

Bu tablo bize bütün loopback IP'lerinin, bütün router'lar arasındaki bağlantı IP'lerinin ve en arkadaki PC networklerinin başarılı bir şekilde routerlar arasında taşındığını göstermektedir. Tabloya göre R-04 **1.1.1.1/32** networküne **130 cost** değeri ile erişmekteydi. OSPF bu hesabı yaparken aşağıdaki formülü kullanmaktadır.

Cost = 100,000,000 / Bandwidth (bps)

Bu formülde bahsi geçen **Bandwidth** değerleri efektif/güncel/anlık değer değildir. Bilginin gelmiş olduğu ilgili interface'in sabit değeridir. Tabiki değiştirilebilir.

R-04#**show interfaces serial 0/0/0**

```
Serial0/0/0 is up, line protocol is up (connected)
  Hardware is HD64570
  Internet address is 172.16.34.4/24
    MTU 1500 bytes, BW 1544 Kbit, DLY 20000 usec,
      reliability 255/255, txload 1/255, rxload 1/255
    Encapsulation HDLC, loopback not set, keepalive set (10 sec)
    Last input never, output never, output hang never
    Last clearing of "show interface" counters never
    Input queue: 0/75/0 (size/max/drops); Total output drops: 0
    Queueing strategy: weighted fair
    Output queue: 0/1000/64/0 (size/max total/threshold/drops)
      Conversations 0/0/256 (active/max active/max total)
      Reserved Conversations 0/0 (allocated/max allocated)
      Available Bandwidth 1158 kilobits/sec
    5 minute input rate 54 bits/sec, 0 packets/sec
    5 minute output rate 54 bits/sec, 0 packets/sec
      163 packets input, 11372 bytes, 0 no buffer
      Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
      0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
      148 packets output, 10432 bytes, 0 underruns
      0 output errors, 0 collisions, 1 interface resets
      0 output buffer failures, 0 output buffers swapped out
      0 carrier transitions
    DCD=up  DSR=up  DTR=up  RTS=up  CTS=up
```

R-04#

Peki bu **130** değerine nasıl ulaşıldı. En başta R-01 **1.1.1.1/32** networküne (bu bir loopback interface networkü olduğu için) cost 1 ile erişmeye olduğunu R-02'ye bildirir. R-02 gelen bu bilgiye (cost=1'e) bilgiyi aldığı interface'in cost değeri olan 1'i ekler (R-02'nin Gig 0/1 interface'sinin cost değeri 1'dir). Böylelikle R-02 1.1.1.1/32 networküne cost=2 ile erişmeye olduğunu routing tablosuna ekler. R-02 bu bilgiyi R-03'e gönderdiğinde R-03 aldığı cost=2 değerinin üzerine, bilgiyi aldığı interface'in yani Serial 0/0/0'ın cost değeri olan 64'ü ekler (Serial interface'lerin cost değerleri 64'dür). Böylelikle R-03 artık 1.1.1.1/32 networküne cost=66 ile erişmeye olduğunu routing tablosuna ekler. R-03 bu bilgiyi R-04'e gönderdiğinde R-04 aldığı cost=66 değerinin üzerine, bilgiyi aldığı interface'in yani Serial 0/0/0'ın cost değeri olan 64'ü ekler. Böylelikle R-04 artık 1.1.1.1/32 networküne **cost=130** ile erişmeye olduğunu routing tablosuna eklemiştir.

Popüler Interface bandwidth değerleri için **Cost** karşılıkları aşağıdaki gibidir.

Interface Type	$10^8/\text{bps} = \text{Cost}$
Fast Ethernet and faster	$10^8/100,000,000 \text{ bps} = 1$
Ethernet	$10^8/10,000,000 \text{ bps} = 10$
E1	$10^8/2,048,000 \text{ bps} = 48$
T1	$10^8/1,544,000 \text{ bps} = 64$
128 kbps	$10^8/128,000 \text{ bps} = 781$
64 kbps	$10^8/64,000 \text{ bps} = 1562$
56 kbps	$10^8/56,000 \text{ bps} = 1785$



Reference Bandwidth değerinin **100 Mbps** olması ne yazık ki Gigabit ve ötesi interface'lerinde cost karşılıklarının 1 olmasını gerektirmektedir. Bu problemi gidermek için yanlı Gigabit ve ötesi interface'lerin farklı cost değerleri alması için üç farklı çözüm vardır.

Birincisi OSPF konfigurasyonu altında **Reference Bandwidth** değerini değiştirmektir.

```
R(config) #router ospf 1
R(config-router) #auto-cost reference-bandwidth XXX
```

İkincisi Interface konfigurasyonu altında **Bandwidth** değerini değiştirmektir.

```
R(config) #interfaces serial 0/0/0
R(config-if) #bandwidth XXX
```

Üçüncüsü ve en güzel en mantıklı en işe yarar olanı ise Interface konfigurasyonu altında **OSPF Cost** değerini değiştirmektir.

```
R(config) #interfaces serial 0/0/0
R(config-if) # ip ospf cost XXX
```

Birde router R-03'de IP Routing tablosuna bakalım.

R-03#**show ip route**

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2
* - candidate default, U - per-user static route, o - ODR
P - periodic downloaded static route

Gateway of last resort is not set

```
        1.0.0.0/32 is subnetted, 1 subnets
O IA    1.1.1.1/32 [110/66] via 172.16.23.2, 00:02:48, Serial0/0/0
      2.0.0.0/32 is subnetted, 1 subnets
O       2.2.2.2/32 [110/65] via 172.16.23.2, 00:03:16, Serial0/0/0
      3.0.0.0/32 is subnetted, 1 subnets
C       3.3.3.3/32 is directly connected, Loopback0
      4.0.0.0/32 is subnetted, 1 subnets
O       4.4.4.4/32 [110/65] via 172.16.34.4, 00:02:58, Serial0/0/1
      5.0.0.0/32 is subnetted, 1 subnets
O IA    5.5.5.5/32 [110/66] via 172.16.34.4, 00:01:57, Serial0/0/1
      6.0.0.0/32 is subnetted, 1 subnets
O IA    6.6.6.6/32 [110/66] via 172.16.34.4, 00:01:57, Serial0/0/1
      7.0.0.0/32 is subnetted, 1 subnets
O IA    7.7.7.7/32 [110/129] via 172.16.34.4, 00:01:57, Serial0/0/1
      172.16.0.0/16 is variably subnetted, 7 subnets, 2 masks
O IA    172.16.12.0/24 [110/65] via 172.16.23.2, 00:03:16, Serial0/0/0
C     172.16.23.0/24 is directly connected, Serial0/0/0
L     172.16.23.3/32 is directly connected, Serial0/0/0
C     172.16.34.0/24 is directly connected, Serial0/0/1
L     172.16.34.3/32 is directly connected, Serial0/0/1
O IA    172.16.40.0/24 [110/65] via 172.16.34.4, 00:02:58, Serial0/0/1
O IA    172.16.47.0/24 [110/128] via 172.16.34.4, 00:02:58, Serial0/0/1
O IA 192.168.10.0/24 [110/66] via 172.16.23.2, 00:02:48, Serial0/0/0
O IA 192.168.20.0/24 [110/66] via 172.16.34.4, 00:01:57, Serial0/0/1
O IA 192.168.30.0/24 [110/129] via 172.16.34.4, 00:01:57, Serial0/0/1
O IA 192.168.40.0/24 [110/66] via 172.16.34.4, 00:01:57, Serial0/0/1
```

R-03#

Şimdi çeşitli çıktılar ile OSPF yapılandırmasının durum bilgilerini inceleyelim.

R-04#**show ip ospf interface**

```
Serial0/0/1 is up, line protocol is up
  Internet address is 172.16.47.4/24, Area 13
    Process ID 4, Router ID 4.4.4.4, Network Type POINT-TO-POINT, Cost: 64
    Transmit Delay is 1 sec, State POINT-TO-POINT, Priority 0
    No designated router on this network
    No backup designated router on this network
    Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
      Hello due in 00:00:06
    Index 1/1, flood queue length 0
    Next 0x0(0)/0x0(0)
    Last flood scan length is 1, maximum is 1
    Last flood scan time is 0 msec, maximum is 0 msec
    Neighbor Count is 1 , Adjacent neighbor count is 1
      Adjacent with neighbor 7.7.7.7
      Suppress hello for 0 neighbor(s)
Loopback0 is up, line protocol is up
  Internet address is 4.4.4.4/32, Area 0
    Process ID 4, Router ID 4.4.4.4, Network Type LOOPBACK, Cost: 1
    Loopback interface is treated as a stub Host
Serial0/0/0 is up, line protocol is up
  Internet address is 172.16.34.4/24, Area 0
    Process ID 4, Router ID 4.4.4.4, Network Type POINT-TO-POINT, Cost: 64
    Transmit Delay is 1 sec, State POINT-TO-POINT, Priority 0
    No designated router on this network
    No backup designated router on this network
    Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
      Hello due in 00:00:06
    Index 3/3, flood queue length 0
    Next 0x0(0)/0x0(0)
    Last flood scan length is 1, maximum is 1
    Last flood scan time is 0 msec, maximum is 0 msec
    Neighbor Count is 1 , Adjacent neighbor count is 1
      Adjacent with neighbor 3.3.3.3
      Suppress hello for 0 neighbor(s)
GigabitEthernet0/0 is up, line protocol is up
  Internet address is 172.16.40.4/24, Area 12
    Process ID 4, Router ID 4.4.4.4, Network Type BROADCAST, Cost: 1
    Transmit Delay is 1 sec, State DROTHER, Priority 1
    Designated Router (ID) 6.6.6.6, Interface address 172.16.40.6
    Backup Designated Router (ID) 5.5.5.5, Interface address 172.16.40.5
    Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
      Hello due in 00:00:06
    Index 4/4, flood queue length 0
    Next 0x0(0)/0x0(0)
    Last flood scan length is 1, maximum is 1
    Last flood scan time is 0 msec, maximum is 0 msec
    Neighbor Count is 2, Adjacent neighbor count is 2
```

```

Adjacent with neighbor 6.6.6.6 (Designated Router)
Adjacent with neighbor 5.5.5.5 (Backup Designated Router)
Suppress hello for 0 neighbor(s)

```

R-04#

R-02#**show ip ospf interface**

```

GigabitEthernet0/1 is up, line protocol is up
  Internet address is 172.16.12.2/24, Area 11
    Process ID 22, Router ID 2.2.2.2, Network Type BROADCAST, Cost: 1
    Transmit Delay is 1 sec, State BDR, Priority 1
    Designated Router (ID) 1.1.1.1, Interface address 172.16.12.1
    Backup Designated Router (ID) 2.2.2.2, Interface address 172.16.12.2
    Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
      Hello due in 00:00:02
    Index 1/1, flood queue length 0
    Next 0x0(0)/0x0(0)
    Last flood scan length is 1, maximum is 1
    Last flood scan time is 0 msec, maximum is 0 msec
    Neighbor Count is 1, Adjacent neighbor count is 1
      Adjacent with neighbor 1.1.1.1 (Designated Router)
    Suppress hello for 0 neighbor(s)
Loopback0 is up, line protocol is up
  Internet address is 2.2.2.2/32, Area 0
    Process ID 22, Router ID 2.2.2.2, Network Type LOOPBACK, Cost: 1
    Loopback interface is treated as a stub Host
Serial0/0/0 is up, line protocol is up
  Internet address is 172.16.23.2/24, Area 0
    Process ID 22, Router ID 2.2.2.2, Network Type POINT-TO-POINT, Cost: 64
    Transmit Delay is 1 sec, State POINT-TO-POINT, Priority 0
    No designated router on this network
    No backup designated router on this network
    Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
      Hello due in 00:00:09
    Index 3/3, flood queue length 0
    Next 0x0(0)/0x0(0)
    Last flood scan length is 1, maximum is 1
    Last flood scan time is 0 msec, maximum is 0 msec
    Neighbor Count is 1 , Adjacent neighbor count is 1
      Adjacent with neighbor 3.3.3.3
    Suppress hello for 0 neighbor(s)

```

R-02#

R-02#**show ip ospf neighbor**

Neighbor ID	Pri	State	Dead Time	Address	Interface
1.1.1.1	1	FULL/DR	00:00:37	172.16.12.1	GigabitEthernet0/1
3.3.3.3	0	FULL/ -	00:00:32	172.16.23.3	Serial0/0/0

R-02#

R-02#**show ip ospf**

Routing Process "ospf 22" with ID 2.2.2.2
Supports only single TOS(TOS0) routes
Supports opaque LSA
It is an area border router
SPF schedule delay 5 secs, Hold time between two SPFs 10 secs
Minimum LSA interval 5 secs. Minimum LSA arrival 1 secs
Number of external LSA 0. Checksum Sum 0x000000
Number of opaque AS LSA 0. Checksum Sum 0x000000
Number of DCbitless external and opaque AS LSA 0
Number of DoNotAge external and opaque AS LSA 0
Number of areas in this router is 2. 2 normal 0 stub 0 nssa
External flood list length 0

Area 11

Number of interfaces in this area is 1
Area has no authentication
SPF algorithm executed 6 times
Area ranges are
Number of LSA 16. Checksum Sum 0x0888fb
Number of opaque link LSA 0. Checksum Sum 0x000000
Number of DCbitless LSA 0
Number of indication LSA 0
Number of DoNotAge LSA 0
Flood list length 0

Area BACKBONE (0)

Number of interfaces in this area is 2
Area has no authentication
SPF algorithm executed 5 times
Area ranges are
Number of LSA 14. Checksum Sum 0x05950b
Number of opaque link LSA 0. Checksum Sum 0x000000
Number of DCbitless LSA 0
Number of indication LSA 0
Number of DoNotAge LSA 0
Flood list length 0

R-02#

R-04#**show ip ospf neighbor**

Neighbor ID	Pri	State	Dead Time	Address	Interface
5.5.5.5	1	FULL/BDR	00:00:35	172.16.40.5	GigabitEthernet0/0
6.6.6.6	1	FULL/DROTHER	00:00:31	172.16.40.6	GigabitEthernet0/0
3.3.3.3	0	FULL/ -	00:00:38	172.16.34.3	Serial0/0/0
7.7.7.7	0	FULL/ -	00:00:39	172.16.47.7	Serial0/0/1

R-04#

R-01#**show ip ospf database**

OSPF Router with ID (1.1.1.1) (Process ID 1)

Router Link States (Area 11)

Link ID	ADV Router	Age	Seq#	Checksum	Link count
1.1.1.1	1.1.1.1	1055	0x80000004	0x008299	3
2.2.2.2	2.2.2.2	1055	0x80000003	0x00f0bb	1

Net Link States (Area 11)

Link ID	ADV Router	Age	Seq#	Checksum
172.16.12.2	2.2.2.2	1055	0x80000001	0x00c11

Summary Net Link States (Area 11)

Link ID	ADV Router	Age	Seq#	Checksum
2.2.2.2	2.2.2.2	1052	0x80000001	0x00fa53
172.16.23.0	2.2.2.2	1052	0x80000002	0x004af7
3.3.3.3	2.2.2.2	1052	0x80000003	0x004bbc
172.16.34.0	2.2.2.2	1052	0x80000004	0x004fa5
4.4.4.4	2.2.2.2	1042	0x80000005	0x009b26
172.16.47.0	2.2.2.2	1042	0x80000006	0x003e67
172.16.40.0	2.2.2.2	1042	0x80000007	0x0011d9
7.7.7.7	2.2.2.2	992	0x80000008	0x008de4
192.168.30.0	2.2.2.2	992	0x80000009	0x00d134
5.5.5.5	2.2.2.2	992	0x8000000a	0x006d4a
192.168.40.0	2.2.2.2	992	0x8000000b	0x00e652
6.6.6.6	2.2.2.2	992	0x8000000c	0x003b76
192.168.20.0	2.2.2.2	992	0x8000000d	0x00bf8b

R-01#

R-02#**show ip ospf database**

OSPF Router with ID (2.2.2.2) (Process ID 22)

Router Link States (Area 0)

Link ID	ADV Router	Age	Seq#	Checksum	Link count
2.2.2.2	2.2.2.2	1249	0x80000003	0x00da0a	3
3.3.3.3	3.3.3.3	1234	0x80000005	0x007eec	5
4.4.4.4	4.4.4.4	1231	0x80000003	0x003b79	3

Summary Net Link States (Area 0)

Link ID	ADV Router	Age	Seq#	Checksum
172.16.12.0	2.2.2.2	1264	0x80000001	0x004d40
172.16.47.0	4.4.4.4	1237	0x80000001	0x00071c
172.16.40.0	4.4.4.4	1231	0x80000002	0x00d98e
192.168.10.0	2.2.2.2	1224	0x80000002	0x003fa1
1.1.1.1	2.2.2.2	1224	0x80000003	0x002f20
7.7.7.7	4.4.4.4	1171	0x80000003	0x005699
192.168.30.0	4.4.4.4	1171	0x80000004	0x009ae8
5.5.5.5	4.4.4.4	1171	0x80000005	0x0036fe
192.168.40.0	4.4.4.4	1171	0x80000006	0x00af07
6.6.6.6	4.4.4.4	1171	0x80000007	0x00042b
192.168.20.0	4.4.4.4	1171	0x80000008	0x008840

Router Link States (Area 11)

Link ID	ADV Router	Age	Seq#	Checksum	Link count
2.2.2.2	2.2.2.2	1229	0x80000003	0x00f0bb	1
1.1.1.1	1.1.1.1	1229	0x80000004	0x008299	3

Net Link States (Area 11)

Link ID	ADV Router	Age	Seq#	Checksum
172.16.12.2	2.2.2.2	1229	0x80000001	0x00call

Summary Net Link States (Area 11)

Link ID	ADV Router	Age	Seq#	Checksum
2.2.2.2	2.2.2.2	1226	0x80000001	0x00fa53
172.16.23.0	2.2.2.2	1226	0x80000002	0x004af7
3.3.3.3	2.2.2.2	1226	0x80000003	0x004bbc
172.16.34.0	2.2.2.2	1226	0x80000004	0x004fa5
4.4.4.4	2.2.2.2	1216	0x80000005	0x009b26
172.16.47.0	2.2.2.2	1216	0x80000006	0x003e67
172.16.40.0	2.2.2.2	1216	0x80000007	0x0011d9
7.7.7.7	2.2.2.2	1166	0x80000008	0x008de4
192.168.30.0	2.2.2.2	1166	0x80000009	0x00d134
5.5.5.5	2.2.2.2	1166	0x8000000a	0x006d4a
192.168.40.0	2.2.2.2	1166	0x8000000b	0x00e652
6.6.6.6	2.2.2.2	1166	0x8000000c	0x003b76
192.168.20.0	2.2.2.2	1166	0x8000000d	0x00bf8b

R-03#**show ip ospf database**

OSPF Router with ID (3.3.3.3) (Process ID 3)

Router Link States (Area 0)

Link ID	ADV Router	Age	Seq#	Checksum	Link count
2.2.2.2	2.2.2.2	1360	0x80000003	0x00da0a	3
3.3.3.3	3.3.3.3	1345	0x80000005	0x007eec	5
4.4.4.4	4.4.4.4	1345	0x80000003	0x003b79	3

Summary Net Link States (Area 0)

Link ID	ADV Router	Age	Seq#	Checksum
172.16.12.0	2.2.2.2	1375	0x80000001	0x004d40
172.16.47.0	4.4.4.4	1348	0x80000001	0x00071c
172.16.40.0	4.4.4.4	1342	0x80000002	0x00d98e
192.168.10.0	2.2.2.2	1335	0x80000002	0x003fa1
1.1.1.1	2.2.2.2	1335	0x80000003	0x002f20
7.7.7.7	4.4.4.4	1282	0x80000003	0x005699
192.168.30.0	4.4.4.4	1282	0x80000004	0x009ae8
5.5.5.5	4.4.4.4	1282	0x80000005	0x0036fe
192.168.40.0	4.4.4.4	1282	0x80000006	0x00af07
6.6.6.6	4.4.4.4	1282	0x80000007	0x00042b
192.168.20.0	4.4.4.4	1282	0x80000008	0x008840

R-03#

R-04#**show ip ospf database**

OSPF Router with ID (4.4.4.4) (Process ID 4)

Router Link States (Area 0)

Link ID	ADV Router	Age	Seq#	Checksum	Link count
2.2.2.2	2.2.2.2	1493	0x80000003	0x00da0a	3
4.4.4.4	4.4.4.4	1478	0x80000003	0x003b79	3
3.3.3.3	3.3.3.3	1478	0x80000005	0x007eec	5

Summary Net Link States (Area 0)

Link ID	ADV Router	Age	Seq#	Checksum
172.16.47.0	4.4.4.4	1481	0x80000001	0x00071c
172.16.12.0	2.2.2.2	1508	0x80000001	0x004d40
172.16.40.0	4.4.4.4	1476	0x80000002	0x00d98e
192.168.10.0	2.2.2.2	1468	0x80000002	0x003fa1
1.1.1.1	2.2.2.2	1468	0x80000003	0x002f20
7.7.7.7	4.4.4.4	1415	0x80000003	0x005699
192.168.30.0	4.4.4.4	1415	0x80000004	0x009ae8
5.5.5.5	4.4.4.4	1415	0x80000005	0x0036fe
192.168.40.0	4.4.4.4	1415	0x80000006	0x00af07
6.6.6.6	4.4.4.4	1415	0x80000007	0x00042b
192.168.20.0	4.4.4.4	1415	0x80000008	0x008840

Router Link States (Area 12)

Link ID	ADV Router	Age	Seq#	Checksum	Link count
4.4.4.4	4.4.4.4	1425	0x80000002	0x000956	1
6.6.6.6	6.6.6.6	1425	0x80000004	0x00b2e1	3
5.5.5.5	5.5.5.5	1425	0x80000004	0x005c31	3

Net Link States (Area 12)

Link ID	ADV Router	Age	Seq#	Checksum
172.16.40.6	6.6.6.6	1425	0x80000002	0x0067a1

Summary Net Link States (Area 12)

Link ID	ADV Router	Age	Seq#	Checksum
172.16.47.0	4.4.4.4	1481	0x80000001	0x00071c
7.7.7.7	4.4.4.4	1415	0x80000002	0x005898
192.168.30.0	4.4.4.4	1415	0x80000003	0x009ce7
4.4.4.4	4.4.4.4	1415	0x80000004	0x005cde
172.16.34.0	4.4.4.4	1415	0x80000005	0x008e9d
172.16.23.0	4.4.4.4	1415	0x80000006	0x00896c
3.3.3.3	4.4.4.4	1415	0x80000007	0x0007f4
2.2.2.2	4.4.4.4	1415	0x80000008	0x00b509
172.16.12.0	4.4.4.4	1415	0x80000009	0x0006f6
192.168.10.0	4.4.4.4	1415	0x8000000a	0x00f758
1.1.1.1	4.4.4.4	1415	0x8000000b	0x00e7d6

Router Link States (Area 13)

Link ID	ADV Router	Age	Seq#	Checksum	Link count
4.4.4.4	4.4.4.4	1446	0x80000003	0x00bded	2
7.7.7.7	7.7.7.7	1446	0x80000004	0x00389e	4

Summary Net Link States (Area 13)

Link ID	ADV Router	Age	Seq#	Checksum
172.16.40.0	4.4.4.4	1476	0x80000001	0x00db8d
4.4.4.4	4.4.4.4	1415	0x80000002	0x0060dc
172.16.34.0	4.4.4.4	1415	0x80000003	0x00929b
172.16.23.0	4.4.4.4	1415	0x80000004	0x008d6a
3.3.3.3	4.4.4.4	1415	0x80000005	0x000bf2
2.2.2.2	4.4.4.4	1415	0x80000006	0x00b907
172.16.12.0	4.4.4.4	1415	0x80000007	0x000af4
192.168.10.0	4.4.4.4	1415	0x80000008	0x00fb56
1.1.1.1	4.4.4.4	1415	0x80000009	0x00ebd4
5.5.5.5	4.4.4.4	1415	0x8000000a	0x002c04
192.168.40.0	4.4.4.4	1415	0x8000000b	0x00a50c
6.6.6.6	4.4.4.4	1415	0x8000000c	0x00f930
192.168.20.0	4.4.4.4	1415	0x8000000d	0x007e45

R-04#

R-05#**show ip ospf database**

OSPF Router with ID (5.5.5.5) (Process ID 5)

Router Link States (Area 12)

Link ID	ADV Router	Age	Seq#	Checksum	Link count
6.6.6.6	6.6.6.6	1522	0x80000004	0x00b2e1	3
5.5.5.5	5.5.5.5	1522	0x80000004	0x005c31	3
4.4.4.4	4.4.4.4	1522	0x80000002	0x000956	1

Net Link States (Area 12)

Link ID	ADV Router	Age	Seq#	Checksum
172.16.40.6	6.6.6.6	1522	0x80000002	0x0067a1

Summary Net Link States (Area 12)

Link ID	ADV Router	Age	Seq#	Checksum
172.16.47.0	4.4.4.4	1578	0x80000001	0x00071c
7.7.7.7	4.4.4.4	1512	0x80000002	0x005898
192.168.30.0	4.4.4.4	1512	0x80000003	0x009ce7
4.4.4.4	4.4.4.4	1512	0x80000004	0x005cde
172.16.34.0	4.4.4.4	1512	0x80000005	0x008e9d
172.16.23.0	4.4.4.4	1512	0x80000006	0x00896c
3.3.3.3	4.4.4.4	1512	0x80000007	0x0007f4
2.2.2.2	4.4.4.4	1512	0x80000008	0x00b509
172.16.12.0	4.4.4.4	1512	0x80000009	0x0006f6
192.168.10.0	4.4.4.4	1512	0x8000000a	0x00f758
1.1.1.1	4.4.4.4	1512	0x8000000b	0x00e7d6

R-05#

<https://goo.gl/hKPtQd>

R-06#**show ip ospf database**

OSPF Router with ID (6.6.6.6) (Process ID 6)

Router Link States (Area 12)

Link ID	ADV Router	Age	Seq#	Checksum	Link count
6.6.6.6	6.6.6.6	1381	0x80000004	0x00b2e1	3
4.4.4.4	4.4.4.4	1381	0x80000002	0x000956	1
5.5.5.5	5.5.5.5	1381	0x80000004	0x005c31	3

Net Link States (Area 12)

Link ID	ADV Router	Age	Seq#	Checksum
172.16.40.6	6.6.6.6	1381	0x80000002	0x0067a1

Summary Net Link States (Area 12)

Link ID	ADV Router	Age	Seq#	Checksum
172.16.47.0	4.4.4.4	1437	0x80000001	0x00071c
7.7.7.7	4.4.4.4	1371	0x80000002	0x005898
192.168.30.0	4.4.4.4	1371	0x80000003	0x009ce7
4.4.4.4	4.4.4.4	1371	0x80000004	0x005cde
172.16.34.0	4.4.4.4	1371	0x80000005	0x008e9d
172.16.23.0	4.4.4.4	1371	0x80000006	0x00896c
3.3.3.3	4.4.4.4	1371	0x80000007	0x0007f4
2.2.2.2	4.4.4.4	1371	0x80000008	0x00b509
172.16.12.0	4.4.4.4	1371	0x80000009	0x0006f6
192.168.10.0	4.4.4.4	1371	0x8000000a	0x00f758
1.1.1.1	4.4.4.4	1371	0x8000000b	0x00e7d6

R-06#

R-07#**show ip ospf database**

OSPF Router with ID (7.7.7.7) (Process ID 77)

Router Link States (Area 13)

Link ID	ADV Router	Age	Seq#	Checksum	Link count
7.7.7.7	7.7.7.7	1636	0x80000004	0x00389e	4
4.4.4.4	4.4.4.4	1636	0x80000003	0x00bded	2

Summary Net Link States (Area 13)

Link ID	ADV Router	Age	Seq#	Checksum
172.16.40.0	4.4.4.4	1666	0x80000001	0x00db8d
4.4.4.4	4.4.4.4	1605	0x80000002	0x0060dc
172.16.34.0	4.4.4.4	1605	0x80000003	0x00929b
172.16.23.0	4.4.4.4	1605	0x80000004	0x008d6a
3.3.3.3	4.4.4.4	1605	0x80000005	0x00bf2
2.2.2.2	4.4.4.4	1605	0x80000006	0x00b907
172.16.12.0	4.4.4.4	1605	0x80000007	0x000af4
192.168.10.0	4.4.4.4	1605	0x80000008	0x00fb56
1.1.1.1	4.4.4.4	1605	0x80000009	0x00ebd4
5.5.5.5	4.4.4.4	1605	0x8000000a	0x002c04
192.168.40.0	4.4.4.4	1605	0x8000000b	0x00a50c
6.6.6.6	4.4.4.4	1605	0x8000000c	0x00f930
192.168.20.0	4.4.4.4	1605	0x8000000d	0x007e45

R-07#

Dikkatlice bütün router'larda database incelemesi yapılrsa görülecektirki bu son çıktılarında sadece R-05 ve R-06 aynı database'e sahiptir (onlarda aynı area'da oldukları için). Çoklu **area** yapılanmasında olan bütün routerlar farklı **topoloji database'lerine** sahiptirler. Bu noktada en az bir interface'i area 0 da olup diğer interface'leri farklı area/area'larda olan router'lara **Area Border Router (ABR)** denmektedir. ABR'lar çoklu database'lere sahip oldukları için diğerlerine kıyasla daha iyi bir CPU'ya ihtiyaç duyabilirler. Günümüzdeki cihazların CPU yapılanlarında ciddi bir iyileşme olduğu gözlenmekte olsa da topolojinin büyüklüğüne göre bu durumun göz ardı edilmemesi gerekmektedir. Gerçi CPU'lardaki bu iyileşme bizlere **area** yapılanmasını da gereksiz kılmaktadır. Günümüzde çok sayıda cihazın tek bir area'da çalışacağı öngürülmektedir. Bu noktada net bir sayı mevcut değildir. Bu sayı için CPU ve yapının kendisine has değişkenler göz önünde bulundurulmalıdır.

Son olarak sadece cisco router'larda görmekte olduğumuz faydalı bir çıktıyı yine buraya taşıyalım:

R-04#**show ip protocols**

Routing Protocol is "ospf 4"
Outgoing update filter list for all interfaces is not set
Incoming update filter list for all interfaces is not set
Router ID 4.4.4.4
Number of areas in this router is 3. 3 normal 0 stub 0 nssa
Maximum path: 4
Routing for Networks:
4.4.4.4 0.0.0.0 area 0
172.16.34.4 0.0.0.0 area 0
172.16.40.4 0.0.0.0 area 12
172.16.47.4 0.0.0.0 area 13
Routing Information Sources:
Gateway Distance Last Update
2.2.2.2 110 00:06:51
3.3.3.3 110 00:06:35
4.4.4.4 110 00:06:03
5.5.5.5 110 00:05:43
6.6.6.6 110 00:05:44
7.7.7.7 110 00:06:04
Distance: (default is 110)

R-04#

R-01#**show ip protocols**

Routing Protocol is "ospf 1"
Outgoing update filter list for all interfaces is not set
Incoming update filter list for all interfaces is not set
Router ID 1.1.1.1
Number of areas in this router is 1. 1 normal 0 stub 0 nssa
Maximum path: 4
Routing for Networks:
192.168.10.1 0.0.0.0 area 11
1.1.1.1 0.0.0.0 area 11
172.16.12.1 0.0.0.0 area 11
Passive Interface(s):
GigabitEthernet0/0
Routing Information Sources:
Gateway Distance Last Update
1.1.1.1 110 00:07:28
2.2.2.2 110 00:07:29
Distance: (default is 110)

R-01#

PC'lerin haberleşmelerine bir bakalım. PC1'den diğerlerine ping atalım.

PC>**ping -n 2 192.168.20.11**

Pinging 192.168.20.11 with 32 bytes of data:

```
Reply from 192.168.20.11: bytes=32 time=2ms TTL=123
Reply from 192.168.20.11: bytes=32 time=11ms TTL=123
```

Ping statistics for 192.168.20.11:

```
    Packets: Sent = 2, Received = 2, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 2ms, Maximum = 11ms, Average = 6ms
```

PC>**ping -n 2 192.168.30.11**

Pinging 192.168.30.11 with 32 bytes of data:

```
Reply from 192.168.30.11: bytes=32 time=3ms TTL=123
Reply from 192.168.30.11: bytes=32 time=3ms TTL=123
```

Ping statistics for 192.168.30.11:

```
    Packets: Sent = 2, Received = 2, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 3ms, Maximum = 3ms, Average = 3ms
```

PC>**ping -n 2 192.168.40.11**

Pinging 192.168.40.11 with 32 bytes of data:

```
Reply from 192.168.40.11: bytes=32 time=2ms TTL=123
Reply from 192.168.40.11: bytes=32 time=12ms TTL=123
```

Ping statistics for 192.168.40.11:

```
    Packets: Sent = 2, Received = 2, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 2ms, Maximum = 12ms, Average = 7ms
```

PC>

Router'ların son config'leri

```
R-01#show running-config
Building configuration...

Current configuration : 1091 bytes
!
version 15.1
no service timestamps log datetime msec
no service timestamps debug datetime msec
no service password-encryption
!
hostname R-01
!
no ip cef
no ipv6 cef
!
license udi pid CISCO2901/K9 sn FTX1524ALVY
!
no ip domain-lookup
!
spanning-tree mode pvst
!
interface Loopback0
  ip address 1.1.1.1 255.255.255.255
!
interface GigabitEthernet0/0
  ip address 192.168.10.1 255.255.255.0
  duplex auto
  speed auto
!
interface GigabitEthernet0/1
  ip address 172.16.12.1 255.255.255.0
  duplex auto
  speed auto
!
interface Serial0/0/0
  no ip address
  clock rate 2000000
  shutdown
!
interface Serial0/0/1
  no ip address
  clock rate 2000000
  shutdown
!
```

```
!
interface Vlan1
  no ip address
  shutdown
!
router ospf 1
  router-id 1.1.1.1
  log-adjacency-changes
  passive-interface GigabitEthernet0/0
  network 192.168.10.1 0.0.0.0 area 11
  network 1.1.1.1 0.0.0.0 area 11
  network 172.16.12.1 0.0.0.0 area 11
!
ip classless
!
ip flow-export version 9
!
line con 0
  exec-timeout 0 0
  logging synchronous
!
line aux 0
!
line vty 0 4
  login
!
end
```

```
R-02#show running-config
Building configuration...

Current configuration : 1052 bytes
!
version 15.1
no service timestamps log datetime msec
no service timestamps debug datetime msec
no service password-encryption
!
hostname R-02
!
no ip cef
no ipv6 cef
!
license udi pid CISCO2901/K9 sn FTX15240R13
!
no ip domain-lookup
!
spanning-tree mode pvst
!
interface Loopback0
  ip address 2.2.2.2 255.255.255.255
!
interface GigabitEthernet0/0
  no ip address
  duplex auto
  speed auto
  shutdown
!
interface GigabitEthernet0/1
  ip address 172.16.12.2 255.255.255.0
  duplex auto
  speed auto
!
interface Serial0/0/0
  ip address 172.16.23.2 255.255.255.0
  clock rate 2000000
!
interface Serial0/0/1
  no ip address
  clock rate 2000000
  shutdown
!
interface Vlan1
  no ip address
  shutdown
```

```
!
router ospf 22
  router-id 2.2.2.2
  log-adjacency-changes
  network 172.16.12.2 0.0.0.0 area 11
  network 2.2.2.2 0.0.0.0 area 0
  network 172.16.23.2 0.0.0.0 area 0
!
ip classless
!
ip flow-export version 9
!
line con 0
  exec-timeout 0 0
  logging synchronous
!
line aux 0
!
line vty 0 4
  login
!
end
```

```
R-03#show running-config
Building configuration...

Current configuration : 1031 bytes
!
version 15.1
no service timestamps log datetime msec
no service timestamps debug datetime msec
no service password-encryption
!
hostname R-03
!
no ip cef
no ipv6 cef
!
license udi pid CISCO2901/K9 sn FTX1524073W
!
no ip domain-lookup
!
spanning-tree mode pvst
!
interface Loopback0
  ip address 3.3.3.3 255.255.255.255
!
interface GigabitEthernet0/0
  no ip address
  duplex auto
  speed auto
  shutdown
!
interface GigabitEthernet0/1
  no ip address
  duplex auto
  speed auto
  shutdown
!
interface Serial0/0/0
  ip address 172.16.23.3 255.255.255.0
!
interface Serial0/0/1
  ip address 172.16.34.3 255.255.255.0
  clock rate 2000000
!
interface Vlan1
  no ip address
  shutdown
!
```

```
!
router ospf 3
  router-id 3.3.3.3
  log-adjacency-changes
  network 172.16.23.3 0.0.0.0 area 0
  network 3.3.3.3 0.0.0.0 area 0
  network 172.16.34.3 0.0.0.0 area 0
!
ip classless
!
ip flow-export version 9
!
line con 0
  exec-timeout 0 0
  logging synchronous
!
line aux 0
!
line vty 0 4
  login
!
end
```

```
R-04#show running-config
Building configuration...

Current configuration : 1080 bytes
!
version 15.1
no service timestamps log datetime msec
no service timestamps debug datetime msec
no service password-encryption
!
hostname R-04
!
no ip cef
no ipv6 cef
!
license udi pid CISCO2901/K9 sn FTX1524UDPU
!
no ip domain-lookup
!
spanning-tree mode pvst
!
interface Loopback0
  ip address 4.4.4.4 255.255.255.255
!
interface GigabitEthernet0/0
  ip address 172.16.40.4 255.255.255.0
  duplex auto
  speed auto
!
interface GigabitEthernet0/1
  no ip address
  duplex auto
  speed auto
  shutdown
!
interface Serial0/0/0
  ip address 172.16.34.4 255.255.255.0
!
interface Serial0/0/1
  ip address 172.16.47.4 255.255.255.0
  clock rate 2000000
!
interface Vlan1
  no ip address
  shutdown
!
```

```
!
router ospf 4
  router-id 4.4.4.4
  log-adjacency-changes
  network 172.16.47.4 0.0.0.0 area 13
  network 4.4.4.4 0.0.0.0 area 0
  network 172.16.34.4 0.0.0.0 area 0
  network 172.16.40.4 0.0.0.0 area 12
!
ip classless
!
ip flow-export version 9
!
line con 0
  exec-timeout 0 0
  logging synchronous
!
line aux 0
!
line vty 0 4
  login
!
end
```

```
R-05#show running-config
Building configuration...

Current configuration : 953 bytes
!
version 15.1
no service timestamps log datetime msec
no service timestamps debug datetime msec
no service password-encryption
!
hostname R-05
!
no ip cef
no ipv6 cef
!
license udi pid CISCO2901/K9 sn FTX1524858M
!
no ip domain-lookup
!
spanning-tree mode pvst
!
interface Loopback0
  ip address 5.5.5.5 255.255.255.255
!
interface GigabitEthernet0/0
  ip address 172.16.40.5 255.255.255.0
  duplex auto
  speed auto
!
interface GigabitEthernet0/1
  ip address 192.168.40.1 255.255.255.0
  duplex auto
  speed auto
!
interface Vlan1
  no ip address
  shutdown
!
router ospf 5
  router-id 5.5.5.5
  log-adjacency-changes
  passive-interface GigabitEthernet0/1
  network 5.5.5.5 0.0.0.0 area 12
  network 192.168.40.1 0.0.0.0 area 12
  network 172.16.40.5 0.0.0.0 area 12
!
```

```
!
ip classless
!
ip flow-export version 9
!
line con 0
  exec-timeout 0 0
  logging synchronous
!
line aux 0
!
line vty 0 4
  login
!
end
```

```
R-06#show running-config
Building configuration...

Current configuration : 953 bytes
!
version 15.1
no service timestamps log datetime msec
no service timestamps debug datetime msec
no service password-encryption
!
hostname R-06
!
no ip cef
no ipv6 cef
!
license udi pid CISCO2901/K9 sn FTX1524SUVT
!
no ip domain-lookup
!
spanning-tree mode pvst
!
interface Loopback0
  ip address 6.6.6.6 255.255.255.255
!
interface GigabitEthernet0/0
  ip address 172.16.40.6 255.255.255.0
  duplex auto
  speed auto
!
interface GigabitEthernet0/1
  ip address 192.168.20.1 255.255.255.0
  duplex auto
  speed auto
!
interface Vlan1
  no ip address
  shutdown
!
router ospf 6
  router-id 6.6.6.6
  log-adjacency-changes
  passive-interface GigabitEthernet0/1
  network 6.6.6.6 0.0.0.0 area 12
  network 192.168.20.1 0.0.0.0 area 12
  network 172.16.40.6 0.0.0.0 area 12
!
```

```
!
ip classless
!
ip flow-export version 9
!
line con 0
  exec-timeout 0 0
  logging synchronous
!
line aux 0
!
line vty 0 4
  login
!
end
```

```
R-07#show running-config
Building configuration...

Current configuration : 1072 bytes
!
version 15.1
no service timestamps log datetime msec
no service timestamps debug datetime msec
no service password-encryption
!
hostname R-07
!
no ip cef
no ipv6 cef
!
license udi pid CISCO2901/K9 sn FTX1524XHL7
!
no ip domain-lookup
!
spanning-tree mode pvst
!
interface Loopback0
  ip address 7.7.7.7 255.255.255.255
!
interface GigabitEthernet0/0
  ip address 192.168.30.1 255.255.255.0
  duplex auto
  speed auto
!
interface GigabitEthernet0/1
  no ip address
  duplex auto
  speed auto
  shutdown
!
interface Serial0/0/0
  no ip address
  clock rate 2000000
  shutdown
!
interface Serial0/0/1
  ip address 172.16.47.7 255.255.255.0
!
interface Vlan1
  no ip address
  shutdown
!
```

```
!
router ospf 77
  router-id 7.7.7.7
  log-adjacency-changes
  passive-interface GigabitEthernet0/0
  network 7.7.7.7 0.0.0.0 area 13
  network 192.168.30.1 0.0.0.0 area 13
  network 172.16.47.7 0.0.0.0 area 13
!
ip classless
!
ip flow-export version 9
!
line con 0
  exec-timeout 0 0
  logging synchronous
!
line aux 0
!
line vty 0 4
  login
!
end
```

<https://goo.gl/lYzfSG>

Umarım faydalı bir LAB çalışması olmuştur.
Soru ve yorumlarınız için,
aliaydemir80@gmail.com