

- R1 ve R5 Sadece Loopback 0 interfacerini OSPF'e redistribute edecekler.
- R8 Loopback{80..85} interfacerini redistribute edecek.
- ✓ R4 ve R7 in routing tabloları:

```
R04#show ip route ospf
<...>
Gateway of last resort is 192.168.34.3 to network 0.0.0.0

O*IA 0.0.0.0/0 [110/21] via 192.168.34.3, 00:11:37, Ethernet0/0
      2.0.0.0/32 is subnetted, 1 subnets
O      2.2.2.2 [110/31] via 192.168.34.3, 00:11:37, Ethernet0/0
      3.0.0.0/32 is subnetted, 1 subnets
O      3.3.3.3 [110/11] via 192.168.34.3, 00:11:37, Ethernet0/0
      6.0.0.0/32 is subnetted, 1 subnets
O IA   6.6.6.6 [110/41] via 192.168.34.3, 00:10:55, Ethernet0/0
      7.0.0.0/32 is subnetted, 1 subnets
O IA   7.7.7.7 [110/41] via 192.168.34.3, 00:11:20, Ethernet0/0
      8.0.0.0/32 is subnetted, 1 subnets
O IA   8.8.8.8 [110/105] via 192.168.34.3, 00:11:10, Ethernet0/0
O     192.168.12.0/24 [110/30] via 192.168.34.3, 00:11:37, Ethernet0/0
O     192.168.13.0/24 [110/20] via 192.168.34.3, 00:11:37, Ethernet0/0
O IA  192.168.15.0/24 [110/30] via 192.168.34.3, 00:11:37, Ethernet0/0
O IA  192.168.51.0/24 [110/30] via 192.168.34.3, 00:11:37, Ethernet0/0
O IA  192.168.56.0/24 [110/40] via 192.168.34.3, 00:11:37, Ethernet0/0
O IA  192.168.57.0/24 [110/40] via 192.168.34.3, 00:11:37, Ethernet0/0
O IA  192.168.68.0/24 [110/50] via 192.168.34.3, 00:10:55, Ethernet0/0
O IA  192.168.78.0/24 [110/104] via 192.168.34.3, 00:11:20, Ethernet0/0
R04#
```

```
R07#show ip route ospf
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       a - application route
       + - replicated route, % - next hop override

Gateway of last resort is 192.168.57.5 to network 0.0.0.0

O*IA 0.0.0.0/0 [110/11] via 192.168.57.5, 00:13:11, Ethernet0/0
      8.0.0.0/32 is subnetted, 1 subnets
O      8.8.8.8 [110/65] via 192.168.78.8, 00:13:00, Serial1/0
R07#
```